



INSTALLATION INSTRUCTIONS

Installation instructions for Ford Raptor front bumper

*Inspect bumper before installation. Contact Body Armor directly if missing any items 951-808-0750

Hardware List:

1/2" x 1.75"-1.5 hex head bolts Qty: 4

1/2" x 2.25"-1.5 hex head bolts Qty: 2

1/2" flat washers Qty: 12

1/2" lock washers Qty: 6

1/2 Hex nut Qty: 6

5/16" x 1" hex bolt Qty: 18

5/16" flat washers Qty: 20

5/16" lock washers Qty: 2

5/16" hex nuts Qty: 2

Kit Includes:

Front bumper

Belly pan (preinstalled)

Upper light brackets Qty: 2

**DSF-3101 winch plate sold separately

Removing Factory front bumper:

Step 1 Locate factory bolts and remove all hardware. Also remove the factory skid plate. Once all the hardware is removed pull the bumper off of the vehicle

Prep Body Armor bumper for installation:

*If installing a winch, you will need to place the haus fairlead behind the front fascia. Secure with tape or wire ties. Remove the tape or ties after the bumper and winch plate are connected with the 2.25" 1/2" bolts

*A roller fairlead will need to mount to the front of the bumper

*Pre-install 6" dual LED lights behind the slotted area in the fascia of the bumper. Use light tabs provided by the lighting company

*Remove the factory tow hooks if installing winch plate ONLY

*If installing a winch: Mount winch to winch plate, then pre-install the winch plate to the vehicle.



INSTALLATION INSTRUCTIONS

Installing front bumper:

Step 1 Remove the two inner bolts located on the front of the cross member. The belly pan brace attaches using these bolts

Step 2 Locate the 1.75" 1/2" bolts, Qty of 4, place flat washer on the head side of the bolts. Have two flat washers lock washers and nuts set on the ground near each frame horn. With a helper lift the bumper to the vehicle.

Step 3 Line up the bumper mounting plates so that the holes on the frame horns line up with the holes in the bracket. Loosely attach the bumper to the frame horns. Note: There are four holes in our brackets per side and only two holes in the factory frame horns per side. We provide the extra mounting holes for those that choose to beef up the installation. Using these extra mounting points will require drilling into the frame horns and we do not provide the extra hardware. We do not require the additional mounting points this is at owner discretion.

Step 4 Attach the belly-pan arms to the cross member by using the factory bolts that were removed previously.

Step 5 If installing winch plate, use the 1/2"x2.25" bolts to tie the bumper to the winch plate well. Remove temporary tape

Step 6 Install front license plate with the holes provided (non winch installation)

Lighting options:

*Our bumper is designed to hold a 30" light bar under the center hoop. We provide light brackets for this installation

*6" dual LED's can be installed behind the grill pattern areas of the bumper

*Two cube LED lights, or 3" round lights can be mounted in each bumper wing

*Up to four 7" round halogen, LED or HID lamps can be mounted on the light tabs on the top hoop.

Paint: We have selected a high-quality DuPont Mini Tex paint and have added two coats of a zinc based powder primer. By doing this we believe that we have provided the most durable paint combination in the industry. Like your vehicle to keep the beauty of the paint it will require maintenance on the user's part. So be sure to touch up scratches whenever possible. Deep scratches can lead to rust and possibly peeling of the powder coat. Use a quality flat black spray paint. Apply the paint to a piece of foam or paper and dab it on the scratched area.